VAP VAPORMATIC

Vapormatic UK. Ltd, Kestrel Way, Sowton Industrial Estate, Exeter, EX2 7LA

Tel: +44 (0)1392 684000

Fax: +44 (0)1392 438445

www.vapormatic.com

New Product Update & Parts Information

****

| Bulletin	UK	Export	Issued
1373	YES	YES	2/7/2018

LED Trailer lighting

Vapormatic has expanded its range of LED trailer lights, bolstering the selection of LED warning lights, beacons and work lights on offer. The new range of trailer lights offers applications for a wide range of vehicles in attractive, modern slim-line designs.

All lights feature high intensity LEDs, offering low current draw for efficient power consumption and longer working life.

To support LED vehicle lighting conversion, Vapormatic has introduced a Canbus friendly LED resistor kit.

ADD THIS:

Canbus LED Resistor	Part No: VLC2361
	Get rid of errors and fault codes with this LED resistor. With easy installation this product offers a convenient solution when converting to LED lighting.

![Vapormatic Logo] **VAP VAPORMATIC**

Vapormatic UK. Ltd, Kestrel Way, Sowton Industrial Estate, Exeter, EX2 7LA

Tel: +44 (0)1392 684000

Fax: +44 (0)1392 438445
www.vapormatic.com

New Product Update & Parts Information

****

Bulletin	UK	Export	Issued
1373	YES	YES	2/7/2018

LED Burger Combination Lights

Part No: VLC2374
Replacement LED rear combination light. Requires plastic mounting base.

Part No: VLC2375
Replacement LED fog light. Requires plastic mounting base.

Part No: VLC2376
Replacement LED reverse light. Requires plastic mounting base.

Part No: VLC2377
Replacement LED rear combination light. Includes plastic mounting base

	VLC2374	VLC2375	VLC2376	VLC2377	VLC2362
Profile	Rear Combination Light	LED Fog Light	LED Reverse Light	Rear Combination Light	Plastic Mounting Base
Function	Stop / Tail / Indicator	Fog	Reverse	Stop / Tail / Indicator	N/A
Reg Approval	E and EMC	E and EMC	E and EMC	E and EMC	
Voltage	9-30V	9-30V	9-30V	9-30V	
IP Rating	IP67	IP67	IP67	IP67	
Lens Material	Polycarbonate	Polycarbonate	Polycarbonate	Polycarbonate	
No. of High-Intensity LEDs	20	20	20	20	
Dimension	140L x 140W x 30Hmm	140L x 140W x 30Hmm	140L x 140W x 30Hmm	140L x 140W x 30Hmm	
Notes	Requires additional plastic mounting base	Requires additional plastic mounting base	Requires additional plastic mounting base	Includes plastic mounting base	Includes fixings

VAP VAPORMATIC

Vapormatic UK. Ltd, Kestrel Way, Sowton Industrial Estate, Exeter, EX2 7LA

Tel: +44 (0)1392 684000

Fax: +44 (0)1392 438445
www.vapormatic.com

New Product Update & Parts Information

****

Bulletin	UK	Export	Issued
1373	YES	YES	2/7/2018

LED Combination Rear Lights

Part No: VLC2363
Rectangular LED rear combination light. Includes surface mounted bracket, only 28mm deep making it perfect for small trailers.

Part No: VLC2364
Compact, square combination light with stop, tail, indicator and number plate functions.

Part No: VLC2365
6 function, vertical triangle LED combination light. Modern slim line and chrome design – just 25mm deep. Right hand fitment only.

Part No: VLC2366
6 function, vertical triangle LED combination light. Modern slim line and chrome design – just 25mm deep. Left hand fitment only.

	VLC2363	VLC2364	VLC2365	VLC2366
Profile	Rectangular rear combination light	Square rear combination light	RH Vertical triangle combination light – 6 function	LH Vertical triangle combination light – 6 function
Function	Stop / Tail / Indicator	Stop / Tail / Indicator / No. Plate	Stop / Tail / Indicator / Reflector / Reverse / Fog	Stop / Tail / Indicator / Reflector / Reverse / Fog
Reg Approval	E and EMC	E and EMC	E and EMC	E and EMC
Voltage	10-30V	12/24V	10-30V	10-30V
IP Rating	IP67	IP67	IP67	IP67
Lens Material	Polycarbonate	Polycarbonate	Polycarbonate	Polycarbonate
No. of High-Intensity LEDs	24	10	39	39
Dimension	190L x 85W x 28Hmm	100L x 100W x 50Hmm	218L x 147W x 25Hmm	218L x 147W x 25Hmm
Fixing	Includes surface-mounted bracket	150mm cable	45cm cable, stud mounted	45cm cable, stud mounted
Notes	28mm deep, good for small trailers		LED replacement for Aspock Earpoint 3 bulb lamps	LED replacement for Aspock Earpoint 3 bulb lamps

VAP VAPORMATIC

Vapormatic UK. Ltd, Kestrel Way, Sowton Industrial Estate, Exeter, EX2 7LA

Tel: +44 (0)1392 684000

Fax: +44 (0)1392 438445

www.vapormatic.com

New Product Update & Parts Information

****

Bulletin	UK	Export	Issued
1373	YES	YES	2/7/2018

LED Combination Rear Lights

Part No: VLC2378
Rectangular, 270mm (10.5") wide LED rear combination light with stop, tail, indicator and fog light functions. Includes surface-mount bracket. Just 35mm deep. Suitable replacement for Ifor Williams trailers.

Part No: VLC2379
Rectangular, 270mm (10.5") wide LED rear combination light with stop, tail, indicator and reverse light functions. Includes surface-mount bracket. Just 35mm deep. Suitable replacement for Ifor Williams trailers.

	VLC2378	**VLC2379**
Profile	Rectangular rear combination light	Rectangular rear combination light
Function	Stop / Tail / Indicator and Fog Light	Stop / Tail / Indicator / Reverse Light
Reg Approval	E and EMC	E and EMC
Voltage	10-30V	10-30V
IP Rating	IP67	IP67
Lens Material	Impact resistant polycarbonate	Impact resistant polycarbonate
No. of High-Intensity LEDs	75	75
Dimension	270mm wide x 90mm high x 35mm deep	270mm wide x 90mm high x 35mm deep
Fixing	Includes 40cm cable. Horizontal or vertical mount	Includes 40cm cable. Horizontal or vertical mount
Notes	Suitable replacement for Ifor Williams trailers	Suitable replacement for Ifor Williams trailers

Vapormatic UK. Ltd, Kestrel Way, Sowton Industrial Estate, Exeter, EX2 7LA

Tel: +44 (0)1392 684000

Fax: +44 (0)1392 438445
www.vapormatic.com

New Product Update & Parts Information

****

Bulletin	UK	Export	Issued
1373	YES	YES	2/7/2018

Heavy Duty Stalk Marker Lights

Part No: VLC2367 (RH) & VLC2368 (LH)
Heavy-duty LED stalk marker light. Long 45˚ off-set profile. High quality, flexible rubber stem. Pre-wired with 2 core cable.

Part No: VLC2369 (RH) & VLC2370 (LH)
Heavy-duty LED stalk marker light. Short 45˚ off-set profile. High quality, flexible rubber stem. Pre-wired with 2 core cable. Right hand fitment only.

Part No: VLC2371 (RH) & VLC2372 (LH)
Heavy duty tail / front LED stalk marker light. Curved 90˚ profile. High quality, flexible rubber stem. Pre-wired with 2 core cable.

Part No: VLC6145
LED Side outline marker lamp with rubber base.

	Profile	Reg Approval	Voltage	IP Rating	Dimension	Fixing
VLC2367	RH Long 45 degree, off-set. Red / White	E and EMC	10-24V	IP66	160L x 50W x 90Hmm	21cm cable length, pre-drilled mounting holes
VLC2368	LH Long 45 degree, off-set. Red / White	E and EMC	10-24V	IP66	160L x 50W x 90Hmm	21cm cable length, pre-drilled mounting holes
VLC2369	RH Short 45 degree, off-set. Red / White	E and EMC	10-30V	IP66	110L x 50W x 90Hmm	29cm cable length, pre-drilled mounting holes
VLC2370	LH Short 45 degree, off-set. Red / White	E and EMC	10-30V	IP66	110L x 50W x 90Hmm	29cm cable length, pre-drilled mounting holes
VLC2371	RH Curved 90 degree. Red / White	E and EMC	10-30V	IP66	110L x 50W x 90Hmm	18cm cable length, pre-drilled mounting holes
VLC2372	LH curved 90 degree. Red / White	E and EMC	10-30V	IP66	110L x 50W x 90Hmm	18cm cable length, pre-drilled mounting holes
VLC6145	Side marker lamp. Red / White	E and EMC	10-30V	IP66	69L x 60W x 74.5Hmm	18cm cable length, pre-drilled mounting holes

Bulletin	UK	Export	Issued
1373	YES	YES	2/7/2018

Hazard Lamps

Part No: VLC2373
9W amber LED strobe warning light. Permanent screw mounted with die cast aluminium housing ideal for mounting on the rear of tractors/trailers or other farm machinery. Can be surface or flush mounted. Pre-wired.

Part No: VLC6124
LED screw mounted warning light, features epoxy sealed electrics and long lasting LEDs rated up to 100,000 hours of operation.

Part No: VLC6133
Magnetic LED warning light, easily mounted to give other road users and pedestrians extra warning. Can also be used as a stationary warning light using the flip out stand.

	VLC2373	VLC6124	VLC6133
Profile	9w Amber LED strobe warning light	LED warning light	Magnetic LED warning light
Reg Approval	E, EMC & R65	E and EMC	
Voltage	12/24V	10-30V	4 x AA batteries (not supplied)
IP Rating	IP65	IP67	
Flash Pattern	Multiple flash patterns	Flash mode & constant	Flashing & steady
No. of High-Intensity LEDs	3 x 3W	4 x 3W	18
Dimension	105L x 40W x 30Hmm	100L x 100W x 50Hmm	160L x 100W x 50Hmm
Fixing	85mm hole centres, 4mm mounting holes,14cm cable length	Screw mounted / pedestal mounting brackets	Magnetic base mounts or flip stand